

FORZA™

FR487INDBK

Family Line: 48" Induction Professional Range

48" Professional Model / 7 High-powered Induction Zones

3 Automatic Cooking Modes / 7.8 cu ft single cavity

Matte black color & Luxurious metal finishing

INDUCTION FEATURES

Cooking surface	Ceramic glass
Induction zones	7
Type of control	Knobs
Power zone	
	Front left 2 x Bridge 2100 W (3700 W Booster)
	Rear left 2 x Bridge 2100 W (3700 W Booster)
	Central right Double / Inductor 3000W / 5500W
	Rear right Inductor 1850W / 3000W
	Front right Inductor 2300W / 3700W
Automatic cooking modes	Keep Warm - Meting - Simmering

CONTROL PANEL

User interface	5,4" white LED Display control
Commands	9 Knobs

DISPLAY FEATURES

Clock T° e Function	•
Preset/Last Used	•
Temperature Memory	•
Preheat bar	25%, 50%, 75%, 100%
Automatic Fast Preheat	•
Child Door Lock	•
Sabbath Mode	•
Hour Clock Formats	AM/PM
Degree unit	°F or °C

OVEN FEATURES

Oven type	Dual fan with True Euro Convection and self cleaning
Cavity finishing	FORZA Porcelain grey easy to clean
Rack positions/levels	6
Oven light	2 lateral halogen lamps
Oven door	Tempered edge to edge triple glass
Hinge closing system	Soft closing
Removable inner glass	Yes

OVEN FUNCTIONS

Oven Lights		True European Convection Bake (Multilevel)	
Thaw (defrost)		Convection Broil	
Bake		Broil	
Convection Roast			



DISTINCTIVE FINISHING



INDUCTION COOKING SURFACE



MASSIMORED™ DOUBLE BROILER



FORZA™

INCLUDED ACCESSORIES

Wire shelves	2
Baking tray	1 MassimoRed™ broiler pan with Grill trivet (rack for broiling on tray)
Glides	1 set telescopic glides movable on different levels
Meat Probe	•
Rotisserie	33" rotisserie with a 50 lb. capacity

OPTIONAL ACCESSORIES

FAGP	Griddle / grill Plate
FA48GRT1	48" kit chromed Grid Rack + Telescopic glide rack 1 level
FAPZS	Pizza Stone
FAAFRY	AirFryer



New

AIRFRYER (FAAFRY)

Thanks to its braided mesh shape, which allows the passage of air and heat inside and the combination with True Euro Convection of the oven, the Forza's AirFryer guarantees a uniform cooking of food.

ELECTRICAL REQUIREMENT

ELECTRICAL SUPPLY

120/240 V - 60Hz 17.2 kW 71.6 A*

120/208 V - 60Hz 14.9 kW 71.6 A*

SERVICE

50 Ampere dedicated circuit

POWER CONNECTION

NEMA 14-50P

*Considering all the power consuming features of this appliance. This model is equipped with a Power Limitation System at 50 Amps that will prevent the tripping of circuit breakers in the event of an extreme and unusual power use scenario.

TECHNICAL DRAWING

